

## High Pressure Hose

### High Pressure LPG Hose

350 psi maximum working pressure. UL Listed. 7132-25354E-350 sized for shipment by UPS.

Part no.	Size I.D.	Size O.D.	Spiral/Braid	Wt./100 ft.	Standard Reel Size
7132-25354	1/4"	0.610	4 spirals	15 lbs.	750'
7132-25354E-350	1/4"	0.610	4 spirals	15 lbs.	350'
7132-38354	3/8"	0.760	4 spirals	22 lbs.	300'
7132-50354	1/2"	0.937	4 spirals	31 lbs.	500'
7132-75354	3/4"	1.250	4 spirals	51 lbs.	350'
7132-100354	1"	1.500	4 spirals	62 lbs.	300'
7232-1252	1 1/4"	1.815	2 braids	85 lbs.	300'
7232-1503	1 1/2"	2.156	3 braids	112 lbs.	150'
7232-2003	2"	2.750	3 braids	177 lbs.	100'



7132 Series



7232 Series

### High Pressure LPG Hose - Stainless Steel Reinforced

Rubber cover. 350 psi maximum working pressure. UL Listed. Cut lengths-bulk lots 300' to 400'.

Part no.	Size I.D.	Size O.D.	Braid	Weight/100 ft.	Standard Reel Size
7233-311	5/16"	0.675	1	19 lbs.	450'
7231-751	3/4"	1.25	1	61 lbs.	100'
7231-1001	1"	1.5	1	78 lbs.	100'
7231-1251	1 1/4"	1.75	1	96 lbs.	100'
7231-1501K	1 1/2"	2	1	107 lbs.	150'
7231-2002K	2"	2.625	2	177 lbs.	150'



7233 Series




7231 Series

### High Pressure LPG Carburetion Hose - Stainless Steel Reinforced

Reinforcement: one fiber braid and one stainless steel wire braid. Fiber braid cover. 350 psi maximum working pressure. UL Listed. Cut lengths-bulk lots 300' to 400'.

Part no.	Size I.D.	Size O.D.
FC321-04	1/4"	.52
FC321-06	3/8"	.68
FC321-08	1/2"	.77
FC321-12	3/4"	1.08



## Low Pressure Hose

### Low Pressure General Purpose Hose - Red

LP-Gas vapor-only service. Recommended working pressure 125 psi. Rubber coated.

Part no.	Spirals	Size I.D.	Size O.D.	Weight/100 ft.	Standard Reel Size
7122-382	2	3/8"	21/32"	14.9 lbs.	700'



### LPG Vapor/Water Heater Hose

Part no.	Size I.D.	Standard Package	Pieces
VH-58	5/8"	30'	3
VH-34	3/4"	30'	3
VH-78	7/8"	30'	3
VH-100	1"	30'	3
VH-112	1 1/2"	30'	3

### Vacuum Hose

Part no.	Description
340-VH	Vacuum hose, 3/16" I.D.
341-VH	Vacuum hose, 1/4" I.D.
342-VH	Vacuum hose, 3/8" I.D.

Prices subject to change without notice. Some items may not be in stock at all warehouses or may be special order. Please check with TEECO.

E1

Rev 8/20

### LPG Hose Assemblies



**Low Pressure** - 3/8" ID, 3/8" SAE x 3/8" SAE

Part no.	Hose I.D.	End Fittings	Length
300L-4	3/8"	3/8" SAE x 3/8" SAE	4"
300L-6			6"
300L-10			10"
300L-15			15"
300L-20			20"

**High Pressure** - Working pressure 350 psi, 1750 psi burst rating. Other sizes available upon request.

Part no.	Hose I.D.	End Fittings	Length
360-4	1/2"	1/2" MPT x 1/2" MPT	4'
360-6			6'
360-8			8'
360-10			10'
360-12			12'
360-12 1/2			12½'
360-15			15'
360-18			18'
360-20			20'
360-25			25'
360-30			30'
360-50			50'

Part no.	Hose I.D.	End Fittings	Length
361-1	3/4"	3/4" MPT x 3/4" MPT	1'
361-1 1/2			1½'
361-2			2'
361-3			3'
361-4			4'
361-6			6'
361-10			10'
361-12			12'
361-15			15'
361-18			18'
361-20			20'
361-25			25'
361-50			50'
361-100			100'
361-125			125'
361-150			150'

Note: To order hose lengths that are not listed above, select the Series # for the Hose I.D. you want, then add the hose length to the end. For Example, 360-5 for a 5' hose with 1/2" I.D.

Prices subject to change without notice. Some items may not be in stock at all warehouses or may be special order. Please check with TEECO.

### Ordering

#### Ordering Custom Hose Assemblies

Hydraulically pressed-on hose couplings using pressures in excess of 10,000 psi. For LP-Gas and NH<sub>3</sub> hose assemblies. DOT Tested.

#### How to Order

Determine overall length of hose. Specify part number of hose. See previous page for hose part numbers and pricing. From tables below, specify part number of hose-end coupling for each end and part number for assembly charge.

#### Hose End Couplings

Part no.	Fitting size	For hose Size
HY06-06MP	3/8" MNPT	3/8" I.D.
08MP-08TY	1/2" MNPT	1/2" I.D.
HY12-12MP	3/4" MNPT	3/4" I.D.
16MP-16LAR	1" MNPT	1" I.D.
HY20-20MP	1¼" MNPT	1¼" I.D.
S10143-24-24	1½" MNPT	1½" I.D.
32NP-32LA	2" MNPT	2" I.D.

#### Assembly Charges

Part no.	Description
AC4	1/4" hose assembly charge
AC6	3/8" hose assembly charge
AC8	1/2" hose assembly charge
AC12	3/4" hose assembly charge
AC16	1" hose assembly charge
AC20	1¼" hose assembly charge
AC24	1½" hose assembly charge
AC32	2" hose assembly charge

#### Determining Custom Hose Assy. Cost

Multiply the length of the hose times the cost per foot. Add the cost of each hose end coupling, plus the assembly charge.

#### Example:

You need 10' of 1" LP-Gas hose with 1" male pipe couplings on each end.

Part no.	Description
7132-100354	1" High Pressure Hose X 10 feet
16MP-16LAR	1" MNPT Hose end coupling
16MP-16LAR	1" MNPT Hose end coupling
AC16	1" hose assembly charge

### 1", 1 1/4" and 2" LP-Gas Hose Assemblies

Part no.	Hose I.D.	End Fittings	Length
362-50	1"	1" MPT x 1" MPT	50'
362-X			Various

Note: To specify length, substitute X for the hose length, in feet. For Example, 362-50 for a 50' hose assembly.

Part no.	Hose I.D.	End Fittings	Length
363-5	1 1/4"	1 1/4" MPT x 1 1/4" MPT	5'
363-10			10'
363-12			12'
363-15			15'
363-18			18'
363-20			20'
363-X			Various

Part no.	Hose I.D.	End Fittings	Length
365-10	2"	2" MPT x 2" MPT	10'
365-15			15'
365-16			16'
365-18			18'
365-20			20'
365-25			25'
365-X			Various


Note: To order hose lengths that are not listed, select the Series # for the Hose I.D. you want, then add the hose length to the end. For Example, 363-6 for a 6' hose with 1 1/4" I.D.

### Low Temp / High Temp LP-Gas Bobtail Delivery Hose

#### Fairview / Gas-Flo Bobtail Hose

- 60° F to +140° F Temps Makes Hose Easier to Handle in Colder Temperatures
- Factory Certified Testing Certificates for Every Hose Assembly
- Custom Lengths Available
- CSA Listed, UL Listed

Part no.	Description
F362-100	1" x 100' Bobtail Delivery Hose Assembly
F362-125	1" x 125' Bobtail Delivery Hose Assembly
F362-150	1" x 150' Bobtail Delivery Hose Assembly



### Abrasion & Low Temperature Resistant Hose Assemblies

#### Polar-Flex Hose/CGA Type 1 Bobtail Hose

Designed for superior performance in transferring liquid petroleum gas, even in sub-zero conditions. Flexible, abrasion resistant. Peak efficiency between -50°F and +180°F. Male x Male. UL Approved Hose.

Part no.	I.D.	Length
PF1-100	1"	100'
PF1-125		125'
PF1-150		150'
PF1-175		175'

\*Hose assembly/Coupled/With DOT certification.

#### Thermoid Hose Type 75

Male X Male - Thermo Pro Sur Fitting. UL Approved Hose.



Part no.	I.D.	Length
TY75-100	1"	100'
TY75-125		125'
TY75-150		150'

\*Hose assembly/coupled/With DOT certification.

### Hose Accessories

#### Pig's Tail Protective Wrapping for Hose

Protect your hose investment with Pig's Tail Protective Wrapping. Prevent hose wear due to friction and abrasion. Designed for heavy-duty building and protection. Rounded edges for safe installation. High/low temperature resistance from -40F to 280F.

Part no.	Description
R20SSG	Pigstail wrapping for 3/8" hose
R25SSG	Pigstail wrapping for 1/2" hose
R32SSG	Pigstail wrapping for 3/4" hose
R40SSG	Pigstail wrapping for 1" hose
R50SSG	Pigstail wrapping for 1 1/4" hose
R75SSG	Pigstail wrapping for 2" hose



Prices subject to change without notice. Some items may not be in stock at all warehouses or may be special order. Please check with TEECO.

E3

Rev 8/20

Order Online: [www.teecoproducts.com](http://www.teecoproducts.com)  
e-mail: [info@teecoproducts.com](mailto:info@teecoproducts.com)

Sacramento, CA  
(800) 225-6621

Auburn, WA  
(800) 426-9456

Rapid City, SD  
(800) 843-8660

### Smart-Hose

The Smart-Hose Safety System is built into a stainless steel metal hose to prevent or eliminate the catastrophic consequences of a hose separation resulting from a pull away or major hose rupture. In the event of such an occurrence, *the Smart-Hose Safety System will shutoff the flow of product in both directions, instantly upon hose separation.*



**Custom lengths and options are available. Not all lengths are listed. Smart-Hose Breakaway Assemblies also available. Refurbishing Program available. Contact Teeco for details.**

**E4**

#### DOT Certified 2" LPG Smart-Hose

Textile Braid LPG Hose, DOT Certified, 316 SS, 350 PSI WP Flapper style valve (LL3)

Part #	Description
R09-016-33-0180-0-00-00	2" X 15', FNPT X FNPT
R09-016-32-0180-0-00-00	2" X 15', MNPT X MNPT
R09-016-33-0222-0-00-00	2" X 18' 6", FNPT X FNPT
R09-016-32-0222-0-00-00	2" X 18' 6", MNPT X MNPT
R09-016-33-0228-0-00-00	2" X 19', FNPT X FNPT
R09-016-32-0228-0-00-00	2" X 19', MNPT X MNPT
R09-016-33-0240-0-00-00	2" X 20', FNPT X FNPT
R09-016-32-0240-0-00-00	2" X 20', MNPT X MNPT

#### DOT Certified 1 1/4" LPG Smart-Hose

Textile Braid LPG Hose, 316 SS, 350 PSI WP Poppet style valve (LL1)

Part #	Description
R09-010-33-0180-0-00-00	1 1/4" X 15', FNPT X FNPT
R09-010-33-0180-0-21-21	1 1/4" X 15', MNPT X MNPT
R09-010-33-0222-0-00-00	1 1/4" X 18' 6", FNPT X FNPT
R09-010-33-0222-0-21-21	1 1/4" X 18' 6", MNPT X MNPT
R09-010-33-0228-0-00-00	1 1/4" X 19', FNPT X FNPT
R09-010-33-0228-0-21-21	1 1/4" X 19', MNPT X MNPT
R09-010-33-0240-0-00-00	1 1/4" X 20', FNPT X FNPT
R09-010-33-0240-0-21-21	1 1/4" X 20', MNPT X MNPT

**Note: Hose length listed is overall length, end to end, including fittings.**

### Flexible Stainless Steel Connectors

Stainless steel corrugated metal LP gas hose with a stainless steel braided sleeve. 350 psi working, 1750 psi burst pressure.



Size	Fittings	Part no. w/o Coating	Part no. w/ Coating
1/2" x 18"	Ground Joint Union x MPT	F50-S18	CF50-S18
1/2" x 24"		F50-S24	CF50-S24
3/4" x 18"		F75-S18	CF75-S18
3/4" x 24"		F75-S24	CF75-S24
1" x 18"		F100-S18	CF100-S18
1" x 24"		F100-S24	CF100-S24
1 1/4" x 18"		F125-S18	CF125-S18
1 1/4" x 24"		F125-S24	CF125-S24
1 1/2" x 18"		F150-S18	CF150-S18
1 1/2" x 24"		F150-S24	CF150-S24
2" x 18"		F200-S18	CF200-S18
2" x 24"		F200-S24	CF200-S24
2 1/2" x 18"		F250-S18	CF250-S18
2 1/2" x 24"		F250-S24	CF250-S24
3" x 18"		F300-S18	CF300-S18
3" x 24"		F300-S24	CF300-S24

Size	Fittings	Part no. w/o Coating	Part no. w/ Coating
1/2" x 18"	MPT x MPT	F50-S18S	CF50-S18S
1/2" x 24"		F50-S24S	CF50-S24S
3/4" x 18"		F75-S18S	CF75-S18S
3/4" x 24"		F75-S24S	CF75-S24S
1" x 18"		F100-S18S	CF100-S18S
1" x 24"		F100-S24S	CF100-S24S
1 1/4" x 18"		F125-S18S	CF125-S18S
1 1/4" x 24"		F125-S24S	CF125-S24S
1 1/2" x 18"		F150-S18S	CF150-S18S
1 1/2" x 24"		F150-S24S	CF150-S24S
2" x 18"		F200-S18S	CF200-S18S
2" x 24"		F200-S24S	CF200-S24S
2 1/2" x 18"		F250-S18S	CF250-S18S
2 1/2" x 24"		F250-S24S	CF250-S24S
3" x 18"		F300-S18S	CF300-S18S
3" x 24"		F300-S24S	CF300-S24S

\* Other sizes available upon request.



Coated Connector

Prices subject to change without notice. Some items may not be in stock at all warehouses or may be special order. Please check with TEECO.

**E4**

Rev 8/20

Order Online: [www.teecoproducts.com](http://www.teecoproducts.com)  
e-mail: [info@teecoproducts.com](mailto:info@teecoproducts.com)

Sacramento, CA  
(800) 225-6621

Auburn, WA  
(800) 426-9456

Rapid City, SD  
(800) 843-8660


**High Pressure Hose Fittings**

High pressure fittings are for hoses which have a 350 psi working pressure and 400 lb. pull test.

**Steel Hose Couplings**

Swivel w/hex nut for stainless steel wire reinforced hose.

Part no.	Hose I.D.	End Fitting	Angle
326-6	3/8"	1/4" MPT	Straight
326-6-6	3/8"	3/8" MPT	
20820-4-4	1/4"	1/4" F. Flare	
323-6S	3/8"	3/8" F. Flare	45°
20820-8-8	1/2"	1/2" F. Flare	
27720-4-4	1/4"	1/4" F. Flare	
30003	3/8"	3/8" F. Flare	90°
27720-8-8	1/2"	1/2" F. Flare	
27920-4-4	1/4"	1/4" F. Flare	
30004	3/8"	3/8" F. Flare	90°
27920-8-8	1/2"	1/2" F. Flare	



**Steel Hose-End Swivel Adapters**

Part no.			End Fittings
Straight	45°	90°	
----	9355X2X2	9405X2X2	1/8" FPT x 1/8" MPT
9205X4X4	9355X4X4	9405X4X4	1/4" FPT x 1/4" MPT
9255X4X4	9385X4X4	9455X4X4	1/4" FPT x 1/4" FPT
9205X8X8	9355X8X8	9405X8X8	1/2" FPT x 1/2" MPT
9255X8X8	9385X8X8	9455X8X8	1/2" FPT x 1/2" FPT
9205X12X12	9355X12X12	9405X12X12	3/4" FPT x 3/4" MPT
9255X12X12	9385X12X12	9455X12X12	3/4" FPT x 3/4" FPT
9205X16X16	9355X16X16	9405X16X16	1" FPT x 1" MPT
9255X16X16	9385X16X16	9455X16X16	1" FPT x 1" FPT
9205X20X20	----	----	1 1/4" FPT x 1 1/4" MPT
9205X24X24	----	----	1 1/2" FPT x 1 1/2" MPT
9205X32X32	----	----	2" FPT x 2" MPT



Straight

45°


90°

Prices subject to change without notice. Some items may not be in stock at all warehouses or may be special order. Please check with TEECO.

**Brass Female Swivels**


Includes spud and nut.

Part no.	Hose I.D.	End Fitting
318-1	1/4"	9/16"-8 LH
209ASF-44		1/4" F. Flare
HC-5335		3/8" F. Flare
320-1		1/4" FPT
320-2	3/8"	3/8" FPT



**Brass Female Pipe Rigid**

Part no.	Hose I.D.	End Fitting
HC-5231	1/4"	18" MPT
HC-5632	1/4"	1/4" FPT
325-C	3/8"	3/8" FPT



**Brass Male Pipe Rigid**

Part no.	Hose I.D.	End Fitting
HC-5232	1/4"	1/4" MPT
HC-5233	1/4"	3/8" MPT



**Brass Inverted Flare**

Part no.	Hose I.D.	End Fitting
HC-5133	1/4"	1/4" Inv. Flare



**Throw-Away Cylinder Swivel Adapters**

Part no.	Hose I.D.	End Fitting
G-484	1/4"	Female 1"-20 swivel
G-496	1/4"	Male 1"-20 swivel



**Male POL**

Part no.	Hose I.D.	End Fitting
970JR	1/4"	M. POL, 7/8" hex
G-1683		M. POL, 7/8" hex, XS Flow



970JR

**Soft Nose Handwheel POL End Fittings**

Part no.	POL Type	End Fitting
G-1653	Excess flow	1/4" MPT
G-1653A**		
G-1654	Full flow	1/4" MPT
G-1654A**		
G-1654P*	Full flow	1/4" hose barb
G-1655		
G-1656	Full flow	1/4" hose barb
G-1656A**		



G-1653



G-1656 (not excess flow)


\* In display pack \*\*w/brass handwheel

**E5**

**Low Pressure Hose Fittings**


Designed for hose with working pressure up to 125 psi.  
**Brass Female Swivels**

Part no.	Hose I.D.	End Fitting
HC-4335	1/4"	3/8" F. Flare
HC-4355	3/8"	3/8" F. Flare
HC-4357		1/2" F. Flare



**Brass Female Pipe Rigid**

Part no.	Hose I.D.	End Fitting
HC-4654	3/8"	1/2" FPT



**Brass Male Pipe Rigid**

Part no.	Hose I.D.	End Fitting
HC-4233	1/4"	3/8" MPT
HC-5233*		3/8" MPT
HC-4252	3/8"	1/4" MPT
HC-4253		3/8" MPT



\* HC-5233 includes 7 barb

**Brass SAE Male Flare**

Part no.	Hose I.D.	End Fitting
HC-4835	1/4"	3/8" M. Flare
HC-4855	3/8"	3/8" M. Flare
HC-32014	3/8"	1/2" MPT



**Water Hose Couplings**

Part no.	Hose I.D.	End Fittings
441-4-4	1/4"	1/4" MPT
442-4		1/4" F. Flare
441-6	3/8"	1/4" MPT
441-6-6		3/8" MPT
442-6		3/8" F. Flare
441-8	1/2"	3/8" MPT
441-8-8		1/2" MPT
442-8		1/2" F. Flare
441-10-8	5/8"	1/2" MPT
441-12-12	3/4"	3/4" MPT

Slip-on type.  
Reusable.



**Worm Drive Clamps**

Part no.	Description
MH-4	7/32" to 5/8"
MH-6C	5/16" to 7/8"
HS-10	9/16" to 1 1/16"
HS-16	13/16" to 1 1/16"
HS-24	1 1/16" to 2"
HS-48	2 9/16" to 3 1/2"



**Band-It Clamp System**

**Clamps - Low Pressure - Galvanized Carbon steel**

Part no.	Hose I.D.	Clamp I.D.	Band Width
J-301	1/4"	13/16"	3/8"
J-302	3/8"	13/8"	3/8"

**Steel Plated Hose Menders**

Part no.	Description
F-106	For 1/4" I.D. hose
F-108	For 3/8" I.D. hose



**Steel Hose Nipples**

Part no.	For Hose I.D.	MPT
349955	1/4"	1/8"
342059	1/4"	1/4"
342061	3/8"	1/4"
342065	3/8"	3/8"
342063	3/8"	1/2"
342068	1/2"	3/8"
6704516	1/2"	1/2"
342075	3/4"	3/4"



**Installation Tools**

Part no.	Description
J-020	Pok-It II tool
C-001	Band-It Tool
J-001	Band-It Adapter



J-001



J-020



C-001

**Clamps-High Pressure - Stainless steel**

Part no.	Hose I.D.	Clamp I.D.	Band Width
J-201	1/4"	13/16"	3/8"
J-203	1/4" & 3/8"	1"	1/2"
J-204	3/8" & 1/2"	1 1/4"	1/2"
J-206	3/4" & 1"	1 3/4"	5/8"
J-240	1/4"	3/4"	1/4"
J-241	3/8"	13/8"	1/4"



**Circle Clamps**

Part no.	Description
8CC	Circle Clamp 1/2"
12CC	Circle Clamp 3/4"
9CC	Circle Clamp 9/16"

**Installation Tools**

**Ferrule Vise**

Used for making hose assemblies with barbed inserts and aluminum ferrules. Dies must be ordered separately.



FV-660-T



FV-670-T

Part no.	Description
FV-660-T	Ferrule Vice - Manual
FV-670-T	Ferrule Vice - Air Operated

Part no.		Closed Dia. (in)
Straight Die	Ribbed Die	
FD-662-T-500	FD-664-T-500	.500
FD-662-T-525	FD-664-T-525	.525
FD-662-T-550	FD-664-T-550	.550
FD-662-T-575	FD-666-T-575	.575
FD-662-T-600	FD-666-T-600	.600
FD-662-T-625	FD-666-T-625	.625
FD-662-T-650	FD-666-T-650	.650
FD-662-T-675	FD-666-T-675	.675
FD-662-T-700	FD-666-T-700	.700
FD-662-T-725	FD-666-T-725	.725
FD-662-T-750	FD-666-T-750	.750
FD-662-T-775	FD-666-T-775	.775
FD-662-T-800	FD-666-T-800	.800
FD-662-T-825	FD-666-T-825	.825



Straight Die



Ribbed Die



**Hose Ferrules**

Ferrules must slip on hose snugly for proper crimping.

Part no.	Description
FBL-500	.500" I.D. ferrule
FBL-525	.525" I.D. ferrule
FBL-550	.550" I.D. ferrule for 1/4" hose
FBL-575	.575" I.D. ferrule for 1/4" hose
FBL-600	.600" I.D. ferrule for 1/4" hose
FBL-625	.625" I.D. ferrule for 1/4" hose
FBL-650	.650" I.D. ferrule for 3/8" hose
FBL-675	.675" I.D. ferrule for 3/8" hose
FBL-700	.700" I.D. ferrule for 3/8" low pressure hose
FBL-725	.725" I.D. ferrule for 3/8" low pressure hose

**Hose Crimper**

Portable or bench mount. Complete with five dies for 1/4" - 1 braid through 3/8" - 2 braid hose.



Part no.	Description
855	Hose crimper

**Ferrule Hand Crimper**

5/8" wide two-hole jaw for 3/16" and 1/4" hose.



Part no.	Description
C-1-WE	Ferrule crimper

**Economy Cutter**

Cuts up to 2" rubber or textile reinforced hose (not for wire reinforced), PVC and PE pipe.



Part no.	Description
T135	Hose cutter
BT135	Replacement blade for T135

**Cable Ties**

U.V. resistant.



Part no.	Description
SST-2	Cable tie, 3/8" x 7"

Prices subject to change without notice. Some items may not be in stock at all warehouses or may be special order. Please check with TEECO.

